



**43MR-SCF12-D01**

**4.3-10 Male Right Angle Connector for 1/2" Coaxial Cable, OMNI FIT™ Premium, Polymer claw and compression sealing**

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications. The 4.3-10 connector is an innovative, space-saving RF connection meeting all requirements even under the most severe environmental conditions and not relying on coupling nut torque. Sealing against outer conductor and jacket by means of the polymer claw and 360° compression fit. Multifunctional, self-lubricating HighTech polymer assembly locks on cable corrugation, avoids electrochemical potential differences and compression-fits to the jacket.



OMNI FIT™ Premium Connectors

**FEATURES / BENEFITS**

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Unique NiTin plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

[External Document Links](#)

[Notes](#)

[Installation Instruction](#)

**Technical features**

**GENERAL SPECIFICATIONS**

<b>Transmission Line Type</b>		Coaxial Cable
<b>Cable Size</b>		1/2
<b>Cable Type</b>		Foam Dielectric Superflexible
<b>Model Series</b>		SCF12-50 Series
<b>Connector Interface</b>		4.3-10
<b>Connector Type</b>		OMNI FIT™ PREMIUM Right Angle
<b>Sealing Method</b>		Polymer claw + 360° Compression
<b>Gender</b>		Male

**ELECTRICAL SPECIFICATIONS**

<b>Nominal Impedance, ohms</b>	Ohm	50
<b>3rd Order IM Product @ 2x20 Watts</b>	dBc	-163 ; typical -167
<b>Maximum Frequency</b>	GHz	6.0
<b>VSWR, Return Loss</b>	VSWR (dB)	0 &lt; f ≤ 2.2 GHz: 1.04 (34.2) 2.2 &lt; f ≤ 2.7 GHz: 1.06 (30.7) 2.7 &lt; f ≤ 3.7 GHz: 1.13 (24.3) 3.7 &lt; f ≤ 5.0 GHz: 1.20 (20.8) 5.0 &lt; f ≤ 6.0 GHz: 1.25 (19.1)



**43MR-SCF12-D01**

4.3-10 Male Right Angle Connector for 1/2" Coaxial Cable, OMNI FIT™ Premium, Polymer claw and compression sealing

**MECHANICAL SPECIFICATIONS**

<b>Plating Outer/Inner</b>		NiTin/Silver
<b>Inner Contact Attachment</b>		Basket
<b>Outer Contact Attachment</b>		360° clamping

**ACCESSORIES**

<b>Wrench size front</b>	mm (in)	22 (7/8)
<b>Wrench size rear</b>	mm (in)	22 (7/8)
<b>Trimming Tool</b>		TRIM-SET-S12-D01, TRIM-SCF12-D01-A

**TESTING AND ENVIRONMENTAL**

<b>Waterproof Level</b>		IP68
-------------------------	--	------