

Single Multi-block hanger two layer, with angle member adapter

Single Multi block hanger support systems are designed for organizing bundled runs of coax cable. Each space-saving block securely holds one run of coax, allowing a compact bundle of up to 3x runs to be supported by stacking three blocks.

FEATURES / BENEFITS

- Single Multi Blocks are manufactured of polypropylene providing thermal, chemical and UV resistance in all environments.
- They come including angle member adapter and necessary hardware.
- The angle member adapter fastens the clamp to the tower without drilling.
- The angle member adapter includes a tower member set screw.
- The hanger mounting rod may be located in either of two mounting holes, depending on orientation of the fixing member.
- Compliant to RoHS (EU 2002/95/EC) and CRoHS (China SJ/T11363-2006) i.e. usable on a global basis.



picture shows MBHS78-2-F for illustration purpose

Technical features


GENERAL SPECIFICATIONS		
Product Line		Coaxial Cable Accessories Hybrid Cable Accessories
Product Type		Hanger
Hanger Type		Single Multi-block
Transmission Line Type		LCF12 HCA12-50 HB012
Cable Type		Coaxial Foam Dielectric Hybrid
Color		Black
MECHANICAL SPECIFICATIONS		
Cable Size		1/2
Number of Cable / Waveguide Runs		1 per layer, 2 layers, 2 runs
Configuration		incl. Angle member adapter
Angle member adapter clamping range mm (in)		4 / 24 (0.157 / 0.945)
Angle member adpter threads		2x M8
Material		Metal part: Stainless steel Plastic parts: Polypropylene
Length	mm (in)	155 (6.10) see picture below (L)
Height	mm (in)	50 (1.96) see picture below (H)
Width	mm (in)	50 (1.96) see picture below (W)
Recommended / Maximum Clamp Spacing	m (ft)	0.6 / 1 (2 / 3.25)

MBHS12-2-F REV DATE: 27 Sep 2022 www.rfstechnologies.com



Single Multi-block hanger two layer, with angle member adapter

TEMPERATURE SPECIFICATIONS Operation Temperature °C (°F) -50 to 85 (-58 to 185) °C (°F) **Storage Temperature** -50 to 85 (-58 to 185) **PACKAGING INFORMATION Package Quantity** 10 Weight per piece kg (lb) 0.178 (0.39) Weight per kit kg (lb) 2 (4.41)



External Document Links

Installation Instruction

Notes

www.rfstechnologies.com MBHS12-2-F REV: E REV DATE: 27 Sep 2022