



RSB -Clip with clamp lining for SCF38, CELLFLEX LCF14 and RGC8 cable

FEATURES / BENEFITS

The RSB-Clip is designed for the installation of feeder cables from sizes 1/4" up to 1-5/8". The clip is a universal clamp device and can be used in many mounting configuration. The RSB-Clip is made of stainless steel. The hanger is resistant against all environmental influences. Due to the mechanical construction, a cable deformation is impossible. Therefore, a deterioration of the electrical properties is avoided.



Kit includes 10 RSB Clips & 10 Clamp Liners

Technical features

GENERAL SPECIFICATIONS

| | | |
|-------------------------------|--|---|
| Product Line | | Coaxial Cable Accessories |
| Product Type | | Hanger |
| Hanger Type | | RSB-Clip (incl. clamp lining) |
| Transmission Line Type | | SCF38 RGC8 LCF14 |
| Cable Type | | Superflexible Coaxial Foam Dielectric Braid/Foil Shield Coaxial Foam Dielectric |

MECHANICAL SPECIFICATIONS

| | | |
|---|---------|---|
| Cable Size | | 3/8 |
| Number of Cable / Waveguide Runs | | 1 |
| Material | | Clamp: Stainless steel Clamp lining: EPDM rubber |
| Drill Hole Size | mm (in) | 8 (0.315) |

ACCESSORIES

| | | |
|--|--|--|
| Spare Part / Useful Accessories | | Cleat : RSB-310 Anchor bar fixation : RSB-315 |
|--|--|--|

TEMPERATURE SPECIFICATIONS

| | | |
|------------------------------|---------|-------------------------|
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |

PACKAGING INFORMATION

| | | |
|-------------------------|--|----|
| Package Quantity | | 10 |
|-------------------------|--|----|

External Document Links

Application Note RSB Clip

Notes