

Cable hanger, non-insulated, bolt-on, for 3" coaxial cable

Hanger, non-insulated, bolt-on for coaxial cable HCA300, made of stainless steel, kit of 10

FEATURES / BENEFITS

Stainless steel hangers for supporting coaxial cable to tower. Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot



Technical features

	SPECII	

Product Line	Coaxial Cable Accessories
Product Type	Hanger
Hanger Type	Bolt-On, non-insulated
Transmission Line Type	HCA300
Cable Type	Air Dielectric

MECHANICAL SPECIFICATIONS

Cable Size		3
Number of Cable / Waveguide Runs		1
Material		Stainless Steel
Recommended / Maximum Clamp Spacing	m (ft)	0.8 / 1.2 (2.75 / 4)

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

Package Quantity	10
------------------	----

External Document Links

Notes

If using the Bolt-on hanger series in vertical runs, the hoisting grips need to be kept on the tower.

CLAMP-300 REV : B REV DATE : 01 Oct 2014 www.rfstechnologies.com