

Hoisting Grip for Coaxial Cable and Elliptical Waveguide, Closed Lacing

The hoisting grip consists of a wire mesh with 1 hoisting eye, closed version FEATURES / BENEFITS

Antenna Transmission Line Installation

- Hoisting stockings distribute the force during installation
- It holds the antenna transmission line by means of friction over their complete length
- The closed version (C-Type) is used when top connector is installed after the antenna transmission line is hoisted
- The open version (L-Type) is used where the top connector is installed prior to the hoisting



Technical features

STRUCTURE

| Product Line | Coaxial Cable Accessories, Elliptical Waveguide Accessories | | | |
|------------------------|---|--|--|--|
| Product Type | Hoisting Grip | | | |
| Transmission Line Type | LCF78, HCA78, UCF78, EP100, E105, EP105 | | | |
| Coaxial Cable Type | Air Dielectric, Foam Dielectric | | | |
| Configuration | 1 loop attachment | | | |
| Style | Closed | | | |
| | | | | |

MECHANICAL SPECIFICATIONS

| Material | Stainless steel |
|----------|-------------------|
| Macciai | Stall liess steel |

PACKAGING INFORMATION

| Package Quantity | 1 | |
|------------------|---|--|
| | | |

External Document Links Notes

HOIST1-78C REV : B REV DATE : 24 Jul 2015 www.rfstechnologies.com